


## SPRING 0619



3 - 14 years



3 kids



12.6 m²

### Material specification

- Powder galvanized and powder coated steel construction,
- The platform is made of recycled HDPE panel, resistant to weather conditions
- Steel springs 20 mm, iron phosphorated and powder coated,
- Screws covered with plastic caps and/or stainless steel screws,



**Physical development**




balance



rocking





## Product technical sheet

# SPRING 0619

## Product data

|                                |                                                                                     |
|--------------------------------|-------------------------------------------------------------------------------------|
| Length                         | 100 cm                                                                              |
| Width                          | 100 cm                                                                              |
| Total height                   | 45 cm                                                                               |
| Age group                      | 3 - 14 years                                                                        |
| Number of users                | 3 kids                                                                              |
| Safety zone                    | 12.6 m2                                                                             |
| Free fall height               | <60 cm                                                                              |
| The height of the platforms    | 45 cm                                                                               |
| In accordance with norm EN     | 1176-1:2017                                                                         |
| Weight of the heaviest part    | 29 kg                                                                               |
| Dimensions of the largest part | 100x100x2 cm                                                                        |
| Availability of spare parts    | YES                                                                                 |
| Installation time              | 1,0 h                                                                               |
| Color options                  |  |

Data is subject to change without prior notice.

## Additional information

- equipment intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jinning the head, fingers or any other body parts;
- anchoring on flat surface, 80/70/60 cm deep;
- render is for reference only, the actual appearance of the equipment and its color may vary;

## Guarantee

**30**

30 year guarantee -  
Structural strength of steel  
and stainless steel  
components

**15**

15 year guarantee -  
Structural failure of steel  
and stainless steel, for  
dynamic equipment

**10**

10 year guarantee - Structural  
failure of high density  
polyethylene and high  
pressure laminates  
components

**5**

5 year guarantee - Corrosion of stainless  
steel and hot dip galvanized and powder  
coated components; against bark beetles  
and rot in case of wooden structural  
elements

Detailed information in the guarantee card



## Surfaces according to EN 1176-1:2017

|                                 | Description (mm)             | Layer thickness (cm) | Maximum fall heights (cm) |
|---------------------------------|------------------------------|----------------------|---------------------------|
| Turf/ top layer of soil (A,B,C) | -                            | -                    | ≤100                      |
| bark (A,C)                      | Particle size from 20 to 80  | 30                   | ≤200                      |
|                                 |                              | 40                   | ≤300                      |
| woodchips (A,C)                 | Particle size from 5 to 30   | 30                   | ≤200                      |
|                                 |                              | 40                   | ≤300                      |
| sand or gravel (A,C)            | Particle size from 0,25 to 8 | 30                   | ≤200                      |
|                                 |                              | 40                   | ≤300                      |
| synthetic attested (A,B,C)      | Tested according to EN 1177  |                      | 60                        |

## Product technical sheet

# SPRING 0619

### Amount of safe surface corresponding with free fall height:

HIC <60 12,6 m<sup>2</sup>

Data is subject to change without prior notice.

